

WATER RESOURCES ENGINEERING

N. Tamai

Department of Civil Engineering, Kanazawa University, Kanazawa, Japan

Keywords: Water motion, water cycle, sedimentation, environment, water ethics, flood, drought, biological diversity, basin management

Contents

1. Introduction
 - 1.1. Hydraulics for Rivers
 - 1.2. Hydraulics for Pipe Flows
 - 1.3. Fluvial Hydraulics
 - 1.4. Engineering Hydrology
 - 1.5. Maritime Hydraulics
 2. Recent Development in Water Resources Engineering
 - 2.1. Worldwide Surge of Environmental Concern
 - 2.2. Sustainability of Water Resources Projects
 - 2.3. Hydroinformatics
 - 2.4. Influence of Global Warming
 3. Real Problems in Human Societies
 - 3.1. Flood and Drought
 - 3.2. Dams and Reservoirs
 - 3.3. Hydropower Generation
 4. New paradigm—Water Ethics
 - 4.1. How Water Resources Engineering Satisfies Water Ethics?
 - 4.2. Partnered Approach
 - 4.3. Value of Environment
- Glossary
Bibliography
Biographical Sketch

Summary

Basic technologies in water resources engineering are described in the initial part of this chapter. Hydraulics provides knowledge on the prediction of water stage and of flow velocity under various conditions. Hydraulics also provides tools for design of hydraulic structures in river training works and hydropower production. Hydrology provides techniques to determine design rainfall or design discharge, which is a key factor for the safety level of flood protection projects. Hydrological data are quite important to quantify existing water resources potential, for instance, a reservoir project for irrigation, drinking water, and hydropower production. Maritime hydraulics provides a technical basis for port and harbor construction, protection of beach erosion, and maintenance of waterways, under wave action.

Surge of environmental concern gave impacts in water resources engineering. Environmental hydraulics emerged and became a popular branch of hydraulics.

Environmental hydraulics clarified diffusion and dispersion problems, stratified flows in reservoirs and estuaries, eutrophication in reservoirs and lakes. As eco-compatibility becomes important, eco-hydraulics and eco-hydrology develop in water resources engineering. Global warming affects the grand design of water resources planning and water resources potential. In this sense global warming needs to be understood not only on a global scale but also at regional and local scales.

Statistical data are summarized for catastrophic floods and drought. Tendency is seen that the number of people killed is reducing chronologically for similar intensity of natural hazards as warning system and counter-measures progress. Major facilities for human water use are also summarized. Water ethics is necessary for sound management of water resources because we need to consider not only human benefits but also to conserve ecosystems for sustainability. Equity and value of environment are new fundamental components in water resources engineering in the 21st century.

1. Introduction

Water resources engineering is related to vast areas in analyses on abundance, scarcity, and conservation of terrestrial waters. In this chapter the development of technology is briefly traced and actual projects and facilities to satisfy human needs are described. In the final part key factors for future development in water resources engineering are discussed.

Fluid mechanics provides a mechanical basis to water resources engineering. The main principles utilized are principles of mass conservation, momentum conservation, and energy conservation. To derive a mathematical solution, there is not only the application of basic principles or basic mathematical equations but also initial or boundary conditions. Because water resources engineering is concerned with waters in the hydrosphere of the earth, much knowledge is needed about earth sciences to determine boundary conditions in real problems in water resources engineering. The requirement of familiarity with earth sciences shows distinction of water resources engineering from fluid mechanics which has been developed in other areas of engineering, for instance, fluid mechanics in mechanical engineering, in aeronautics, in chemical engineering, and so on.

Traditional branches of water resources engineering are classified into hydraulics for rivers, hydrology for rivers, and maritime hydraulics.

1.1. Hydraulics for Rivers

Although all great civilizations in Egypt, Mesopotamia, India, and China resorted to water resources development works, the science of hydraulic engineering remained at infant stage till the modern science greeted its birth through the Renaissance. Hydrostatics was then developed during Renaissance. The dynamics of water movement was formulated through the book published by Daniel Bernoulli in 1738.

Hydraulics has been developed through empirical formulae. Epoch-making books that summarize the existing knowledge in an exhausting manner were edited by Weisbach in

1844 and Forchheimer in 1914. They are the pioneers who made efforts to merge theoretical fluid mechanics with empirical hydraulics. The core part of hydraulics for rivers is open channel hydraulics. Open channel flow has a free water surface where the atmosphere directly connects with water. Water depth and flow velocity are the main variables in the analyses by river engineers and a one-dimensional approach has been a traditional development. This is partly because rivers are long enough compared with dimensions in a section and partly because one-dimensional analysis is the only tractable way for a mathematical approach.

The resistance of a surrounding boundary of a stream is explained by the Manning or Chezy formula, in which resistance to flow is proportional to the square of the sectional average of the flow. These empirical formulae are widely used by hydraulic engineers.

For the majority of design purposes in river engineering in steady state analysis the important parameters are spatial variations of velocity and depth. River flow is more complex and as a typical example of unsteady flow there is the tidal flow in estuaries and floods. Near the peak of a flood temporal variation becomes very slow and hence a quasi-steady analysis is still applicable to study these peak flow features. One of the characteristic features of flood flow is that the discharge in a rising limb of the hydrograph is larger than that in a falling limb for the same water stage.

As the resources of electronic computers expanded, numerical simulation became familiar in research and practice and two-dimensional and three-dimensional schemes became available.

River hydraulics provides knowledge of the prediction of water stage and of flow velocity under various conditions, for instance, flow behaviors during flood and backwater curves upstream or downstream of weirs and dams. Such information is vital for design of various hydraulic structures. Flow behaviors in irrigation canals are also analyzed by hydraulics. Detailed velocity estimation along a bank is needed for design of, for instance, revetment works, groins, and so on. In order to operate hydraulic structures we also need hydraulics. Hydraulics is used for the estimation of the discharge from a sluice or other type of gate, and the pressure force exerted on structures. Hydraulic prediction is also necessary for stable maintenance of river channels. As described above river hydraulics provides a mechanical tool for river basin management.

1.2. Hydraulics for Pipe Flows

This branch of hydraulics has been developed in association with water supply, sewerage works, and hydropower generation. Basic equations used for analyses are the same as those for open channel flows but boundary conditions become different because pipe flow has no free surface.

One characteristic feature of a pipe flow is high pressure caused by a transient flow. Under steady conditions pipes are exposed to hydrostatic pressure but when a valve is shut down in a pipe network the momentum of flowing water is changed, which generates additional pressure. In the case of large amount of flowing water utilized for

hydropower generation and when operation is initiated or terminated, large amount of momentum change produces a very high pressure in the conduit system. The phenomenon or associated high pressure is called the water hammer. Steel structures may be made strong enough for excessive pressures but protection such as a relieving open surge tank may be used. Management of pipe systems and treatment of water is crucial in the event of pollution such as *Cryptosporidium* and *Giardia* organisms. They are harmful germs for human health. Chlorination and ozonation is effective to kill them but higher chlorine concentration of chlorine and ozone has a side effect to produce other harmful chemical compounds. In order to solve this dilemma we need risk analysis in present day planning for permanent potable supplies.

1.3. Fluvial Hydraulics

A fundamental nature of natural streams is a boundary that is composed of movable materials, that is, sediment mixture. Morphological characteristics give not only a beautiful diversity to rivers from the standpoint of landscape but also a wide variety to riverine habitats to support biological diversity of the ecosystem. Fluvial hydraulics provides the fundamental knowledge to understand river morphology.

The sediment mixture is formed mainly by weathering of mountain slopes; then it may be moved momentarily or during certain flow conditions. Fluvial hydraulics deals with processes and mechanisms of sediment movement from its source to destination, that is, river mouth to the sea. In fluvial hydraulics analyses of erosion and deposition are central themes. Examples of problems are, erosion at mountain slope and banks, scour around bridge piers, degradation of the riverbed, deposition in reservoirs, and so on.

The sediment components are classified into three, namely, wash load, suspended load, and bed load. Wash load is a very fine component that originates in a river basin and is transported to the sea by a flood and it is not a component of a riverbed. Suspended sediment is the component that loses contact with the bed for long time after it is picked up into suspension by a flow. Bed load is sand, silt, gravel and rock detritus, mainly carried by a stream along its bed. Prediction of sediment transport rate has long been a major target of fluvial hydraulics and uses a probabilistic theory as a new approach to trace the motion of sediment.

The configuration of rivers is neither flat in the vertical plane nor straight in the horizontal plane. Bed forms are categorized by typical scales of a stream. Ripples and dunes are called small-scale bed forms. Sizes of small-scale bed forms are explained in terms of grain size of riverbed and water depth of a stream. Bars are a medium scale deviation and the size of them is related with stream width. A meander is a large-scale deviation of river course in plan view and related to a stream reach. In a reach a couple of riffle-pool systems are seen in actual streams. Fluvial hydraulics explains the mechanism of how a configuration is formed and a classification chart of rivers with controlling factors has been established.

-
-
-

TO ACCESS ALL THE 12 PAGES OF THIS CHAPTER,
Visit: <http://www.eolss.net/Eolss-sampleAllChapter.aspx>

Bibliography

Cargill R. (1998). *Searching for Reasons*, Engineers Australia, Vol. 70, No. 9, pp. 26-29, The Institution of Engineers Australia. [The article reports a two-month search in Sydney on the bugs of Giardia and Cryptosporidium. What the tests found and actions taken are described.]

Rouse H. and Ince S. (1963). *History of Hydraulics*, 91-100, 161-164, 179-180, 223-224, Dover Publications. [This book provides an extensive review of hydraulics since early antiquity, through post-renaissance age, up to modern fluid mechanics.]

The Centre for Research on the Epidemiology of Disasters (2000). *International Disaster Database*, <http://www.cred.be/>, UNIVERSITE CATHOLIQUE DE LOUVAIN, Brussels. [The database provides disaster records in the whole 20th century.]

International Commission on Large Dams (1998). *World Register of Dams*. [The book presents the ranking of large dams in terms of different criteria.]

Water Power and Dam Construction (2000). *Yearbook 2000*, Wilmington Publishing Ltd. [The book provides review and trend of water power in that year.]

Biographical Sketch

N. Tamai is the Professor of River Engineering at Kanazawa University and Professor Emeritus of the University of Tokyo. He was born in 1941 and graduated from the University of Tokyo with B.S. in Civil Engineering in 1964. In October 1966 he joined the University of Tokyo as a research associate. He obtained the degree of the Doctor of Engineering from the University of Tokyo in 1972. He was Professor of the University of Tokyo between July 1983 and March 2002.

He has experiences as a research assistant at the University of California, Berkeley, as a visiting researcher at the University of Stuttgart, the University of Karlsruhe, the University of Western Australia and the Swiss Federal Institutes of Technology, Lausanne, and as a visiting professor at the Swiss Federal Institutes of Technology, Lausanne and the University of Stuttgart.

His research area was initially mixing problems in environmental hydraulics and shifted to river mechanics, for instance, flows in compound channels and meandering channels, and coherent eddies in geophysical flows. In recent fifteen years he extended the area into environmental river engineering including evaluation of fish habitat, interactive process between vegetation and river works, prediction of human impacts on hydrological cycles, and economic evaluation of environmental flows.

He was Chairman of the Section on Education and Professional Development in the International Association of Hydraulic Engineering and Research and now serves as the Chairman of one of three Divisions of IAHR.

He published more than 300 papers with co-workers. He is the single author of four books and editor in chief of six books. He has been serving as a technical expert in many committees of governments and public organizations.