PIPELINE STRUCTURAL INTEGRITY

Roman W. Motriuk

ARCUS Solutions Inc., Stn. D Calgary, Alberta, Canada T2P 2E7

Keywords: Pipeline, structural integrity, pipe material, pressure, stress, vibration, pipesoil interaction, corrosion, erosion, external damage, operation, operating errors, weld flaws, integrity breach, analysis of threats, risk analysis, preventing failures, environment, safety, plan, program, management, training.

Contents

- 1. Pipeline Structural Integrity Definition
- 2. Pipeline Structural Integrity throughout History and Today
- 3. Overview of Potential Factors Leading to Structural Integrity Breach
- 3.1. Internal Pressure
- 3.2. Stresses within the Pipe Wall
- 3.3. Piping Vibration
- 3.4. Pipe-Soil Interaction
- 3.5. Pipeline Material
- 3.6. Pipeline Corrosion and Erosion
- 3.7. Pipeline Weld Flaws
- 3.8. External Damage Third Party
- 3.9. Incorrect Operation and Operating Errors
- 3.10. Earthquake
- 4. Piping Structural Integrity Evaluation
- 5. Integrity Management Programs
- 5.1. Prescriptive Integrity Programs
- 5.2. Performance-Based Integrity Programs
- 6. Pipeline Integrity Breach
- 6.1. Regulatory Response to Pipeline Integrity Breaches
- 7. Analyses Supporting Structural Integrity and Management Programs
- 7.1. Analysis of Threats
- 7.2. Regulatory Prescribed Risk Analysis
- 7.3. Risk Analysis Results
- 8. Preventing Failures
- 9. Pipeline Structural Integrity and Training
- 9.1. The Value of Training
- 9.2. Training Options
- Glossary
- Bibliography

Biographical Sketch

Summary

The process of fluid transportation using pipelines is nearly as old as human history, and transportation systems have always required maintenance to preserve their structural integrity. Today, managing pipeline structural integrity is done using sophisticated

pipeline risk-analyses and powerful and cost effective tools. A breach in pipeline structural integrity significantly impacts the environment and people, and often has a critical effect on business by bringing on economic losses due to disruption of delivery of the product, costs of cleanup efforts, etc.

Since common threats to pipeline structural integrity cannot be eliminated, they need to be evaluated and managed by means of a devised plan or program which is usually legislated (e.g. in USA, Canada, UK). Such a plan or program must be developed by professional engineers using recent expertise to analyse, detect, evaluate, mitigate or eliminate the risks to the pipeline operations.

It also needs to conform to the defined pipeline requirements such as standards, specifications, material orders, drawings, and documented maintenance philosophy. A good integrity management program must be supported by a competent workforce, regular inspections and appropriate training programs.

1. Pipeline Structural Integrity Definition

From an engineering standpoint, pipeline structural integrity can be defined as the preservation of both the individual parts as well as their mutual relation in an intact state. For this to occur, the stresses at all points and the deflections both local and overall must be kept within safe limits for the specific construction material.

In other words, the pipeline must be designed in such a way that it is able to safely withstand all the external and internal loads, including its own weight and all dynamic forces. In addition, the quality of all parts must be inspected at the time of installation. Then, the pipeline must be managed through proper operation, regular inspections, risk assessment and suitable improvements to maintain its safe condition.

Pipeline structural integrity, as other structural integrities, can be defined loosely within the framework of safety and financial terms. For example, Dr. Steve Roberts of Oxford University states that structural integrity is *'the science and technology of the margin between safety and disaster'* [17]. Further Dr. James, in his paper [24], defines the major drivers for the structural integrity implementation which are primarily financial, involving the desire for operators and investors to maximize return on investment, the desire of insurers to have a pre-defined risk and the possibility of litigation in the event of failure.

An 'industrial' definition of structural pipeline integrity is to maintain the pipeline in as close to new condition as economically feasible.

Usually a breach in pipeline structural integrity leads to a failure which significantly impacts the environment and people and often has a critical effect on business. Apart from human aspects (death, injury, lawsuits) and regulatory restrictions (imposed new pipeline operation limits), a breach of structural integrity brings immediate economic losses due to disruption of delivery of the product, possible shutdown of manufacturing facilities, limitation of transportation services, cleaning up the area of spill, etc. To prevent failures and their consequences, a plan or program is usually developed which

uses engineering expertise to analyse, detect, evaluate, mitigate or eliminate the risks to the pipeline operations. Such a program approach must conform to the defined pipeline requirements such as standards, specifications, material orders, drawings, and documented maintenance philosophy. These requirements along with the competent workforce ensure the effective operation of the pipeline.

2. Pipeline Structural Integrity throughout History and Today

The process of fluid transportation is nearly as old as human history. There are references to the Egyptians using copper pipe to transport water in 3000 BC. According to Advanced Water Distribution Modeling and Management, the first enclosed tubular pipes were constructed in the ancient city of Knossos on the island of Crete in 1500 BC.

From the early stages of civilization the developed societies transported first water and subsequently other liquids and gases for their utilization. Also, wastes were first primitively conveyed by means of ditches and later on, during Roman times, by complicated buried channel systems, see Figure 1.

The Romans developed water distribution systems, parts of which are used even today. There were eleven major aqueducts built in Rome between 312 B.C and 226 A.D, see Figures 2 and 3 [2], the longest of which was 59 miles long. These aqueducts, leading from the water intake in the hills to the distribution cisterns in Rome, consisted mostly of channels bored through the rock.

There was a gradient (less than 1/200) maintained throughout the length of the aqueduct, and vertical shafts were bored at intervals to provide ventilation and access. Only the final sections of the aqueducts were raised on arches, in order to give a sufficient head for water distribution. Up until the 6th century A.D., when the power of the Empire began to decline, the aqueduct system was constantly extended and repaired [1, 3]. Then, it was almost destroyed and remained inactive (except for the one aqueduct which ran entirely underground, *Aqua Virgo*, and a couple of others that were restored during the Middle Ages) until Renaissance times.



Figure 1: Roman sewer systems (photo courtesy of [4])



Figure 2: Roman aqueduct circa 19 BC in southern France today- Pont du Gard (photo courtesy of [2])



Figure 3: Roman aqueduct Valens in Constantinople, Istambul Turkey today; (photo courtesy of [2])

Historically, all of the fluid and gas transportation systems required integrity management which particularly looked into the operation efficiency, cost effectiveness

and the structural soundness of transmission systems.

Today's society is much more demanding and the pipeline transportation industry is focused on more than traditional factors. For example, the foreseeable costs of pipeline operation must include not only those related to possible bursts or leaks but also those which can result from loss of life and property, pollution, or civil and criminal liabilities.

Therefore, managing pipeline structural integrity presents a unique challenge, requiring sophisticated pipeline risk-analyses, know-how of technological advancements and powerful and cost effective tools. This necessitates employing numerous engineering disciplines, such as stress analysis, fatigue and creep analysis, fracture mechanics, metallurgy, corrosion control, non destructive testing, structural monitoring and instrumentation, failure analysis, vibration testing and analyses.

3. Overview of Potential Factors Leading to Structural Integrity Breach

3.1. Internal Pressure

Pipeline integrity requires that the pipeline is able to sustain the pressure load of the conveyed fluid. This requirement calls for evaluating: (i) the minimum necessary pipe wall thickness, and (ii) the pressure rating of the in-line components such as fitting, valves, metering devices and other instruments.

The following steps need to be followed during this process: First, based on the characteristics of the fluid and its service, a suitable piping material is chosen. The pipe diameter and its wall thickness are calculated. In addition, the corrosion, erosion and joint allowance are established as well as the pipe material strength and its mechanical features. Second, the determined pipe size and its wall thickness are compared to the prescribed code's requirements.

In the next step, the standard manufacturing tolerances are compared to the nominal wall thickness with expectation that the tolerance will not reduce the nominal pipe wall thickness to unacceptable values. Finally, the pressure rating based on material properties must be done for the in-line elements in such a way that it exceeds the line requirements. A mandatory non-destructive examination may be carried out for certain elements, e.g. valves, to qualify them for higher pressure rating than the nominal, prescribed by the vendor. This step is dictated for special-class elements and is described in ASME/ANSI B16.34 code.

3.2. Stresses within the Pipe Wall

Stress is defined as the load per unit area within the pipe wall. Piping leading to compressors, pumps, turbines, metering stations, pig launchers, valve stations, boilers, and other facilities must be analysed in order to ensure that

- (i) The stress in piping and machine components meets the required codes
- (ii) The equipment loads meet the specified vendors' allowable values

- (iii) The position of loads on the piping and equipment supports is acceptable
- (iv) The designed life span of structures under cycling loads is sufficient



Figure 4: Stress originated piping explosion; (photo courtesy of [16])

In addition, specific analyses are performed to determine stress in complex parts of equipment or sections of piping subjected to steady state or transient loads such as pressure, thermal displacements, flow excitations, acoustic loads, and vibration loads. Piping analyses are carried out assuming linear or non-linear material behaviour, depending on the studied system's requirements and its operating conditions. There are several failure modes which could damage the piping systems.

A failure mode is defined as the combination of a trigger mechanism and a failure mechanism where the trigger mechanism is an event which initiates the process leading to failure, see Figure 4. During static stress analysis, appropriate codes are used to define processes leading to a failure such as excessive plastic deformation, plastic instability, incremental collapse and high-strain low-cycle fatigue. Stress limits are then calculated according to different codes, which would prevent numerous failure modes.

- -
- -
- -

TO ACCESS ALL THE **46 PAGES** OF THIS CHAPTER, Visit: http://www.eolss.net/Eolss-sampleAllChapter.aspx

Bibliography

1. Anon., 2007, www.inforoma.it: [A brief history of Roman aqueducts].

2. Anon., 2007, http://en.wikipedia.org/wiki/Aqueduct_(Roman) :[A brief history of Roman aqueducts].

3. Anon., 2007, www.unrv.com [History of the Roman Empire including all aspects of social life and politics including building roads, bridges and aqueducts].

4. Anon., 2007, http://users.tellurian.com/tjh/aqua/default.html : [This site describes the need for efficient water transportation in the Roman Empire. With its sudden and immense growth, the Roman Empire soon needed to address the serious problems associated with water. They needed more efficient ways of getting it, and cleaner, more discreet ways of getting rid of waste].

5. Anon., 2007, http://www.corrosion-doctors.org/index.htm : [This site improves the general awareness of the complicated processes that are at play even behind the simplest corrosion reactions and relate these to the impact corrosion may have on systems (e.g. pipelines, cars, boats) and human health (e.g. implants, allergies, toxic metals)].

6. Anon., 2007, http://corrosion.ksc.nasa.gov/eroscor.htm : [This site explains the erosion corrosion phenomenon, which is the result of a combination of an aggressive chemical environment and high fluid-surface velocities].

7. Anon., 2007, www.roseninspection.com_: [This site describes the latest electronic, sensor and robotic technology for pipeline inspection services and pipeline integrity management].

8. Anon., *Alaska Department of Environmental Conservation*, http://www.dec.state.ak.us : [A Government of Alaska website providing information on conservation, improving and protecting Alaska's natural resources; includes news and releases, headlines].

9. Anon., *Alberta Energy and Utility Board, Canada,* www.eub.ca: [A Government of Alberta website providing information on the discovery, development and delivery of Alberta's energy resources and utility services which take place in a manner that is fair, responsible and in the public interest].

10. Anon. (2003-2007) Arcus Solutions Inc., Workshops, Lectures, Reports, Notes, www.arcus-solutions.com: [This site provides information pertinent to piping dynamics, stress, failure analysis and related topics].

11. Anon, *ASTD – Work Place Learning and Performance*, www.astd.org : [Professional Development website which provides contact and training services for different branches of industry].

12. Anon., 2001, *'Managing System Integrity for Hazardous Liquid Lines'*, 1st Edition, ANSI/ASME Standard 1160-2001, November 2001: [The Standard applicable to pipeline systems with ferrous materials that transport liquid and hazardous fluids. The Standard provides the operator with the information necessary to develop and implement an effective integrity management program based on principles and processes pertinent to proven industry practices and processes].

13. Anon., 2001, '*Managing System Integrity of Gas Pipelines*', ASME Code for Pressure Piping, B31, ASME B31.8S-2001; [The Standard applicable to on-shore pipeline systems constructed with ferrous material and which transport gas. The Standard provides the information necessary to develop and implement and effective integrity management program utilizing proven industry practices and processes].

14. Anon., *National Energy Board, Canada*, www.neb.gc.ca : [Website of the Regulatory body of the Government of Canada which provides information on regulatory documents, hearing and information sessions, major energy development applications, conservation, safety and environment, etc.].

15. Anon., *Pipeline Hazardous Management and Safety Administration (old: Office of Pipeline Safety)*, USA, ops.dot.gov : [The Office of Pipeline Safety is the Federal safety authority which ensures the safe, reliable, and environmentally sound operation of the Nation's pipeline transportation system through regulation enforcement, training, research and development and advisory technical committees].

16. Anon., *Pipeline Engineering Centre (PEC), Lectures, Reports, Notes, Materials, etc.* www.eng.ucalgary.ca/PEC/ : [This center's goal is to provide support and direction to industry in pipeline engineering. The center addresses two specific aspects in this endeavor: first, education, and second,

research].

17. Anon, *Structural Integrity Research, Faculty of Technology, University of Plymouth,* www.tech.plymouth.ac.uk (www.plymouth.ac.uk/pages/view.asp?page=9332) ; [This site provides detailed information on structural integrity research which covers a range of activities from numerical modelling of stresses, strains and crack growth phenomena, through residual stress measurements and experimental testing of welded joints, to failure analysis].

18. Anon., *The National Transportation Safety Board*, www.ntsb.gov : [The NTSB is an independent agency charged with determining the probable cause of transportation accidents and promoting transportation safety. This site provides information how to help prevent accidents, save lives and reduce injuries through Board-developed safety recommendations, based on its investigations and studies, which are issued to Federal, State and local government agencies, and to industry and other organizations in a position to improve transportation safety].

19. Biagotti S.F. and S.F.Gosse, 2000, '*Formalizing Pipeline Integrity with Risk Assessment Methods and Tools*', Proceedings of 2000 International Pipeline Conference in Calgary, Alberta, Vol.1 pp.31-39: [Describes how to effectively use risk assessment and management software as well as pipeline inspection tools to maintain the flow of pipeline integrity data to responsible parties].

20. Bughi, S., et al., 1996, 'Slow Movements of Slopes Interfering with Pipelines, "Modeling and Monitoring", Proceedings of 15th International Conference of Offshore Mechanics and Arctic Engineering, Florence, Italy, Vol. 5, pp.363-372.: [Provides information of designing the pipelines which are required to pass through hilly or mountainous areas where slope instability can be a critical issue].

21. Folias, E.S., 1965, 'An Axial Crack in a Pressurized Cylindrical Shell', International Journal of Fracture Mechanics, V1, pp 104-113 : [Provides detailed description on how to evaluate axial cracks in pressurized steel shell structures].

22. Harris, C.M, Crede C.E., 1990, 'Shock and Vibration Handbook', McGraw-Hill Book Company, New York: [Classical textbook describing many aspects of structure dynamics, vibration and noise including seismic analysis techniques].

23. Hopkins, P., 2004, 'Pipeline Integrity: Some Lessons Learnt', WTIA International Pipeline Integrity & Repairs Conference, Welding Technology Institute of Australia, Sydney, Australia: [This paper considers some of the lessons learnt from recent failures and field experiences, and concludes giving a general guidance to all engineers in the pipeline business on operational experience].

24. James, M.N., 'Engineering Materialism and Structural Integrity' Journal of Engineering Design, Vol. 9, No. 4, 1998: [Two prime engineering focuses are concerned with what might be termed `materialism', and with structural reliability. This paper discusses the interconnections between these in the context of the historical development of engineering capability, highlighting the associated risk in application and use of this capability, and the accrued benefits for mankind].

25. Kalis, H.U., Motriuk, R. W., 1997, 'Dynamic Analysis Report for Northwestern Utilities Ltd, Villeneuve Compressor Station, Internal Report: [Describes in detail the inadequacies of the basiclumped element finite element software packages when modelling large diameter piping shells, greater than NPS 24, inches, nominal size].

26. Kastner, W., et al., 1981, 'Critical Crack Sizes in Ductile Piping', International Journal of Pressure Vessels and Piping, v9, pp 197-219: [This article describes the critical crack sizes in pipelines built from ductile ferrous materials, where the author establishes plastic behavior criteria for such piping flaws as gouges].

27. F. Kiefner, et al., 'Analysis of DOT Reportable Incidents for Hazardous Liquid Pipelines', 1986 Through 1996," API Publication 1158, 1999 : [Assessment of pipeline shell critical wall thinning based on two methods: ASME B31.G and the author's research].

28. F. Kiefner, et al., 1996, '*Continued Validation of RSTRENG*', *American Gas Association, Catalog No. L51749:* [Numerical and iterative approach to evaluate critical piping thinning proposed by the author].

29. D. Lyons, 'Western European Cross Country Oil Pipelines 30 year Performance Statistics', CONCAVE, Brussels. Report no. 1/02_www.concave.be: [A comprehensive report on pipeline incidents which were registered over 30 year period in Western Europe, given in a form of statistical information].

30. Motriuk, R.W. and Timothy Schmidt, 2001, '*Rapid, Wide-Field Measurements of Complex Transient Shell Vibrations', Journal of Pressure Vessel Technology, Special Issue on Fluid-Solid Interaction Problems, Vol. 123, No. 4. pp.537-543:* [Describes unique methodology to map and evaluate the complex vibrational fields generated in high power compressor-piping systems].

31. Motriuk, R.W., 1996, 'Verification of Two Methods to Mitigate High Frequency Pipe Shell Vibration', PVP ASME Conference, Flow-Induced Vibration, Montreal, PVP-FIV Volume 328, pp. 405-413: [The author describes how to evaluate in simple terms high frequency piping vibrations and attempts to attenuate them by the addition of mass and stiffness to the piping wall and inserting a pulsation spoiler into the flow stream].

32. Motriuk, R.W., et al., 2000, 'Determination of Dynamic Velocity and Strain Using Wide Field Holographic Interferometry – Verification', Proceedings of International Pipeline Conference, Calgary, 2002, Vol. 2 pp. 1397-1405: [The article describes how to easily judge the level of dynamic strain and stress in piping systems subjected to severe excitations which could not be easily eliminated].

33. Motriuk, R.W., 2000, 'How to Design and Operate Quiet Centrifugal Compressor System', Proceedings of International Pipeline Conference, Calgary, 2002, Vol. 2 pp. 1281-1288: [Describes the last ten years of usage of high power centrifugal compressors which became powerful sources of pulsation, vibration and noise resulting in fatigue or acoustic fatigue of piping attachments and compressor impellers, diffusers and guide vanes. The author presents some guidelines how to avoid such problems].

34. Motriuk, R.W, 2004, 'Assessment of High Frequency Vibrations for TCPL Nordegg Compressor Station, Part I and Part II', Internal Report prepared for TransCanada Pipelines, Calgary, Alberta, Canada: [Detailed description on how to approach and evaluate high-frequency complex vibration in high power piping systems].

35. Mohitpour, M. et al, 2000, '*Pipeline Design and Construction*', *ASME Press, New York:* [This book has evolved from a training course initiated in 1988 in response to the pipeline industry's need. The content of the book, generated by the considerable knowledge and experience of the authors is augmented by current industry practices].

36. 1978, Earthquake Engineering and Soil Dynamics, Proceedings of the ASCE Geotechnical Engineering Division Speciality Conference, Pasadena, California, USA: [This publication is a set of many papers presented at the conference with emphasis on the dynamic behaviour of pipelines under different geotechnical circumstances, including earthquakes].

37. Rizkalla, M et al., 1996, 'Recent Advances in the Modeling of Longitudinal Pipeline Soil Interaction for Cohesive Soils', Proceedings of 15th International Conference of Offshore Mechanics and Arctic Engineering, Florence, Italy, Vol. 5, pp. 325-332: [This article is based on a complex specific study of a "fast' moving slope. One of the large diameter natural gas pipelines of Nova Corporation of Alberta was involved where the piping strain was successfully relieved and the pipeline is still in operation].

Biographical Sketch

Roman W. Motriuk is principal acoustics and structural dynamics engineer with Arcus Solutions Inc. For over 20 years, he has been involved in the oil and gas, power generation, chemical and aeronautic industries while employed by leading companies such as Beta Machinery, Nova Corporation of Alberta, TransCanada and AMEC. His assignments deal with design, troubleshooting and failure analysis of turboand reciprocating machinery, pipelines and its components.

He has extensive experience dealing with stress and fatigue failures, flow and pulsation induced vibration failures, dynamic system stability designs, fluid-solid interaction failures, e nvironmental n oise control and various flow metering problems.

Roman has a M.Sc. degree in Mechanical Engineering specializing in Drilling Machinery from the AGH University of Science and Technology, Cracow, and a M.Sc. degree in Applied Acoustics from the University of Calgary.

He actively participates in research and development projects, and has published ov er thirty scientific papers on vibration, dynamic stress, and turbo-machinery acoustics. For the past several years, he has been teaching courses on pipeline acoustics and compression systems at the University of Calgary.

He is a past chairman of the Calgary Technical Chapter of the ASME-PSD, a member of the international ASME-PSD Executive Committee, and a past co-chair of the International Pipeline Conference (IPC) 2004 Organizing Committee. In addition, he is a member of the Fluid Solid Interaction (FSI) ASME Committee.

SS	
SK RV	
J. An.	