

WATER HARVESTING AND WATER-SAVING TECHNIQUES

Donald Gabriels, Wim M. Cornelis and Wouter Schiettecatte

Department of Soil Management and Soil Care, Ghent University, Belgium

Keywords: China, conservation tillage, conventional tillage, rain-fed agriculture, Tunisia, water harvesting, water saving

Contents

1. Introduction
 2. Review of Some Widely-adopted Water-harvesting and Water-saving Techniques
 - 2.1. Water-harvesting Techniques
 - 2.2. Water-saving Techniques: Conservation Tillage
 3. Case Study: The Jessour System in Tunisia
 4. Case Study: Conservation Tillage on the Loess Plateau of Northern China
 5. Conclusions
- Glossary
Bibliography
Biographical Sketches

Summary

The rainfall regime in drylands is known by its scarcity, unpredictability and torrential character; its water balance is negative during almost the whole year. In order to achieve a reasonable crop production under those conditions and to overcome this drought stress additional water has to be supplied. In this paper, two case studies are presented on the efficient use of rainwater harvesting for the cultivation of trees and crops.

A first case refers to southeast Tunisia, where a *jessr system* is described for collecting runoff water from the slopes of a micro-catchment into a terrace with olive trees. The results of field rainfall simulation tests indicate that large amounts of runoff and sediment can be collected on the terrace. Those amounts depend mainly on the rainfall intensity rather than on the total amount of rainfall of individual events.

A second case deals with the semiarid loess plateau of northeast China, near Luoyang in Henan Province, where the different components of the soil-water balance were analyzed in order to determine the most efficient tillage practice for water saving in winter wheat fields. Subsoiling provided the highest increase in moisture storage and lowest evaporation rates during the fallow period. Because of the presence of a wheat straw mulch, direct sowing resulted in low evaporation and high water storage, particularly at the beginning of the crop-growing season.

The two examples commented in this paper illustrate that water efficiency can still be highly improved in areas where, under natural conditions, water shortage hampers normal crop growth or holds major risks for crop failure.

1. Introduction

Arid and semiarid zones account for approximately one third of the earth's surface and affect some 16% of the population (see *Drylands and Desertification*). In these areas the rainfall regime is known for its scarcity, unpredictability and torrential character, and the water balance is negative almost all year round. Increasing population pressure, hard competition for water resources and the consequences of global warming create additional problems of water scarcity. As rain-fed farming is an important component in agricultural production, it should be supported by additional moisture supplied through rainwater harvesting and rainwater saving techniques (see *Management of Drylands and Desert Areas*).

There are many ways to harvest and store water, including traditional water harvesting techniques and conservation-based cropping systems (see *Desert Reclamation and Management of Drylands: Water Aspects*). In this paper, two case studies are presented where the effects of water harvesting and water-saving techniques were investigated on the soil-water balance in semiarid regions. In a first case study, the effect of a jessr water harvesting system in Amrich, Oued Oum Zessar watershed (South Tunisia) is described and evaluated for its impact on soil and water conservation. The second case reports findings of a field study on winter wheat carried out in the semiarid loess plateau of Northern China, near Luoyang (Henan Province) to compare the soil-water balance under different soil tillage practices.

2. Review of Some Widely-adopted Water-harvesting and Water-saving Techniques

2.1. Water-harvesting Techniques

Four main groups of water harvesting techniques can generally be distinguished: micro- and macro-catchments, floodwater harvesting and storage reservoirs. Typical micro-catchment techniques involve the delineation of natural depressions, the construction of contour and stone bunds, systems for inter-row water harvesting, terracing, construction of semicircular (half moon) and triangular (V-shaped) bunds, eyebrow terraces, Vallerani-type micro-catchments, pits, meskats and negarim.

Macro-catchments include large semi-circular and trapezoidal bunds and hillside conduits. Floodwater can be harvested within the stream bed or diverted to the cropping fields. Storage media include underground storage reservoirs such as soil and sediment, and cisterns, and surface storage media like tanks, jars, ponds and reservoirs. An excellent overview of all these techniques can be found in FAO (2003).

The catchment or water-collection area can be a roof top, a small land surface, a slope or a larger catchment area feeding seasonal water courses.

In southern Tunisia e.g. a large variety of classic water harvesting techniques are used and, as described by Boers and Ben-Asher (1982) and Mainguet (1991), these have been

developed since Antiquity. Ouessar *et al.* (2002) describes the following techniques as most common ones in southern Tunisia:

Jessour - This is an old runoff water harvesting technique widely adopted in arid highlands, which occupies the runoff watercourses. The hydraulic unit of a jessour is the *jessr* consisting of three components: the impluvium, the terrace and the dyke. The impluvium or the catchment area is used for collecting (harvesting) the runoff water. The terrace or the cropping zone is the area where crops or trees are grown and where the runoff water is caught. The dyke is a barrier established to block the sediments and runoff water. Its body is made of earth equipped with a central and/or lateral spillway and one or two abutments. This should assure the evacuation of excess water.

Tabias - This is a replica of the jessour system constructed in the foothill and piedmont areas. It is a relative new technique constructed by mountain dwellers.

Meskat - It is a traditional system consisting of two compartments, a catchment area and a downslope cropping area, both delineated by low bunds. Catchment and cropping area are connected by a spillway.

Floodwater harvesting system - It is an old technique which diverts the total or a portion of the floodwater carried by wadis - dry riverbeds that only contain water during and immediately after heavy rains - to the neighboring cultivated fields, in the form of natural irrigation. It has three components including a diversion dam, a distribution network and the cropping fields. The diversion dam is generally made of earth acting as a fuse by breaking down in case of very intense floods. Recently, gabions (see below) and reinforced concrete are becoming most popular. The distribution network is made of open trapezoidal canals (primary, secondary, tertiary, ...) with gentle slopes except in partition points to avoid silting up. The cropping fields are generally flat with a rectangular shape and delineated by earthen embankments to retain up to 1 m of water.

Gabion units - These units are made of wire mesh cages filled with rock, and are constructed in wadi beds in order to divert water directly to the neighboring fields, often located within the wadi itself.

Recharge wells - These are casing tubes drilled into the underlying bedrock – when of very low permeability – enhancing the infiltration of runoff water to the ground water table. This technique was adopted only recently in Southeastern Tunisia.

Terraces - This very old technique is constructed on steep slopes and consists of small retaining walls made of rocks to slow down the flow rate of the water and to control erosion.

Cisterns - These were traditionally used to provide drinking water. A unit consists of three components, an impluvium, a sediment settling basin and a storage reservoir. The impluvium is a sloping piece of land delineated by a diversion channel or a paved runoff area. The settling basin ahead of the entrance of the cistern allows sedimentation of runoff loads. The storage compartment or cistern consists of a hole dug in the ground, coated with gypsum or concrete, and which is leading to a stone-faced underground small or large-size tank.

2.2. Water-saving Techniques: Conservation Tillage

Besides implementing water harvesting techniques, water can also be saved by applying conservation tillage practices. These include any tillage or tillage and planting combination which leaves 30% or greater cover of crop residue on the surface. Its purpose is to minimize or reduce loss of soil and water. Garcia-Torres *et al.* (2001) have shown that the rate of adoption of conservation tillage for agricultural sustainability is exponentially growing in many regions of the world for the sake of soil and water conservation. Conventional farming practices with extensive cultivation and little use of crop residue exacerbate soil, water and nutrient losses, causing decreases in water availability, soil fertility and crop productivity.

Below is a summary of the most widely adopted conservation tillage practices. More detailed information can be obtained from UN (1999).

Strip cropping - This is the farming of sloping land in alternate, contoured strips of inter-tilled row crops and close growing grasses or another ground cover crop. The strips are aligned at right angles to the direction of the natural runoff flow. The strips slow down the runoff water and filter out soil washed from the land in the inter-tilled row. As a result, infiltration of runoff water will increase and so will be the moisture in the soil. The strip widths can vary depending on the soil type and slope.

Contour farming - This practice involves aligning plant rows and tillage lines at right angles to the normal flow of runoff. The rate of runoff is slowed down, thus giving the water time to infiltrate into the soil. The contour bunds often consist of earth banks 1.5 to 2.0 m wide, and form buffer strips at 10 to 20 m intervals.

Mulch tillage - It is a practice in which the bare soil is covered with mulch or plant litter to reduce the impact energy of rain drops and to minimize the soil evaporation. The mulch is usually made up of crop residues such as wheat straw, sorghum trash or maize stover. When these are not available, or are used by farmers, gravel can be used as a mulch.

Reduced or minimum tillage - This involves the tilling of the soil to some extent, without inverting it completely. Several tools have been developed for reduced tillage, such as ploughs supplemented with discs or a chisel harrow, and non-turning duck-foot erosion plows. As a result, a smaller volume of soil is exposed to erosion and to loss of moisture by evaporation.

Subsoiling - This practice loosens the subsoil by deep plowing, breaks hardpans and facilitates infiltration and aeration of the root zone. Subsoiling allows crop residues to remain on the field without burying it. The residue has the same positive effects as a mulch.

Zero or no tillage - As the word says, land is not tilled at all. Water is conserved in the soil profile since the soil is not tilled and exposed to drying. Weed control is generally

done by applying herbicides. The new crop is generally planted directly into the stubble of the previous crop by direct sowing tools.

-
-
-

TO ACCESS ALL THE 13 PAGES OF THIS CHAPTER,
[Click here](#)

Bibliography

Boers, Th.M. and Ben-Asher, J. (1982). *A Review of Rainwater Harvesting*. Agricultural Water Management, 5, 145-158 [This paper describes a large variety of classic water harvesting techniques used in southern Tunisia].

Cai, X., Wang, X.B. and Gao, X.K. (1998). *Conservation Tillage Systems in Arid Areas of Shouyang*. Chinese Journal of Agricultural Research in the Arid Areas, 3, 41-46 [This article gives an overview of the different conservation tillage techniques that were introduced in northern China – in Chinese with English abstract].

FAO (2003). *Training Course on Water Harvesting for Improved Agricultural Production*. CD-Rom, FAO, Rome. [This CD-ROM is a collection of over 500 PowerPoint slides arranged into four training modules. It gives a complete introduction to water harvesting; from the presentation of various water-harvesting techniques to the details of project management in small communities].

Gao, X.K., Wang, X.B. and Wang, D.S. (1991). *A Study on Tillage Techniques for Soil-Water Storage and Conservation in Rain-fed Wheat Fields*. Chinese Journal of Agricultural Research in Arid Areas 4, 1-9 [This article gives an overview of the different conservation tillage techniques that can be applied in northern China. It was one of the first articles reporting on conservation tillage in China and written by Prof. Gao and colleagues, who is widely recognized as being the primary investigator on conservation tillage in China – in Chinese with English abstract].

García-Torres, L., Benites, J. and Martínez-Vilela, A. (2001). *Conservation Agriculture, A Worldwide Challenge*. Proceedings First World Congress on Conservation Agriculture, 1-5 October 2001, Madrid, Spain [These proceedings give a nice overview of the state-of-the art knowledge on conservation agriculture, including cases studies from numerous countries].

Ouessar, M., Zerrim, A., Boufelgha, M., and Chniter, M. (2002). *Water Harvesting in Southeastern Tunisia: State of Knowledge and Challenges*. Tropical Resource Management Papers 40, 13-24, Wageningen, The Netherlands [This article gives an overview of the different water harvesting techniques currently used in southern Tunisia].

Mainguet, M. (1991). *Desertification: Natural Background and Human Mismanagement*. Springer Verlag, Berlin [A standard work on desertification with references to the natural and human induced causes].

Nearing, M.A., Norton, D.L., Bulgakov, D.A., Larinov, G.A., West, L.T., and Dontsova, K.M. (1997). *Hydraulics and Erosion in Eroding Rills*. Water Resources Research 33(4): 865-876 [This paper outlines the streampower concept for assessing sediment transport on slopes].

Schiettecatte, W., Ouessar, M., Gabriels, D., and Abdelli, F. (2002). *Impacts of Water Harvesting Techniques on Soil and Water Conservation at Field and Sub-Catchment Scale in the Oued Oum Zessar Watershed*. In: de Graaff, N. and Ouessar, M., eds. *Water Harvesting in Mediterranean Zones: An Impact Assessment and Economic Evaluation*. Tropical Resources Management Paper N° 40, 49-60 [This chapter reports the results of field experiments undertaken in a watershed in southern Tunisia to study the impact of a jessour on infiltration, runoff, sediment transport and the soil-water balance].

UN (1999). *Sourcebook of Alternative Technologies for Freshwater Augmentation in Africa*. United Nations, New York, 1999. Technical Publication Series No.:8A [This book gives water resource managers and planners, especially in developing countries and in countries with economies in transition, adequate information on the range of low-cost technologies that can be used for freshwater augmentation].

Vere, D. (2005). *Research into Conservation Tillage for Dryland Cropping in Australia and China*. Australian Centre for International Agricultural Research. Impact Assessment Series Report No. 33 [This book reports on two projects which focused on the development of improved technologies for controlled-traffic farming in dryland crop production in Australia, and on reduced or conservation tillage for similar purposes in China].

Biographical Sketches

Donald Gabriels is professor at the Department of Soil Management and Soil Care of the Faculty of BioScience Engineering of Ghent University, Belgium where he coordinates the Research Group on Soil Erosion and Soil Conservation and the International Center for Eremology (ICE). He is an agricultural engineer of Ghent University and holds a MSc. in agronomy (Soil Physics) of Iowa State University, USA, and a PhD in agricultural engineering of Ghent University. He was a Fulbright postdoctoral scholar at Purdue University, USA.

He has teaching, research and consultancy experience in countries of the five continents in soil and water conservation, water harvesting, soil erosion processes and control, soil physics, soil technology, soil degradation and desertification.

He is founder and co-director of the College on Soil Physics at the Abdus Salam International Center for Theoretical Physics, Trieste, Italy and of ELAFIS (Escuela LatinoAmericana de Física de Suelos).

Wim M. Cornelis is an academic doctor assistant at the Department of Soil Management and Soil Care, and at the Center for Eremology, both at Ghent University, Belgium. He holds a MSc. in agricultural engineering (1992), a MSc. in eremology (1994) and a PhD. in applied biological sciences, land and forest management (2002).

He has 10 years of relevant research and educational experience in soil physics, water and wind erosion, dust pollution, wind tunneling, and soil and water conservation. He was in charge of several missions in developing countries where he was engaged in training activities, research and development related to soil erosion and soil-water management. At present he is Treasurer of the European Soil Science Society.

Wouter Schiettecatte is scientific co-worker at the Department of Soil Management and Soil Care, and at the Center for Eremology, both at Ghent University, Belgium. He holds a MSc. in bioengineering (1997).

He has 5 years of relevant research and educational experience in the field of soil physics, water erosion, and soil and water conservation. He was in charge of several missions in developing countries where he was engaged in training activities, research and development related to soil erosion by water and to soil and water conservation. At present he is working in a soil and water conservation project in the Pinar del Rio province, western Cuba.