

BRIDGE ERECTION MACHINES

Marco Rosignoli

HNTB Corp., USA

Keywords: Beam launchers, self-launching gantries, telescopic gantries, pivoted gantries, overhead and underslung machines, movable scaffolding systems (MSS's), heavy lifters, lifting frames, form travelers, span carriers with underbridge, design loads, modeling, analysis, load testing, instability, robustness, progressive collapse.

Contents

1. Introduction to Bridge Construction Methods
 2. Main Features of Bridge Erection Machines
 3. Beam Launchers
 4. Self-Launching Gantries for Span-By-Span Precast Segmental Erection
 5. Movable Scaffolding Systems (MSS's) for Span-By-Span Casting
 6. Self-Launching Machines for Balanced Cantilever Construction
 7. Carriers and Gantries for Full-Span Precasting
 8. Design Loads of MSS's and Form Travelers
 9. Design Loads of Heavy Lifters
 10. Modeling and Analysis
 11. Instability of 3D Trusses
 12. Instability of Vertical Support Members
 13. Load Testing
 14. Conclusions
- Acknowledgments
Glossary
Bibliography
Bibliographical Sketch

Summary

Bridge industry is moving to mechanized construction because this saves labor, shortens project duration and improves quality. This trend is evident in many countries and affects most construction methods. Mechanized bridge construction is based on the use of special machines.

New-generation bridge erection machines are complex and delicate structures. They handle heavy loads on long spans under the same constraints that the obstruction to overpass exerts onto the final structure. Safety of operations and quality of the final product depend on complex interactions between human decisions, structural, mechanical and electro-hydraulic components of machines, and the bridge being erected.

In spite of their complexity, the bridge erection machines must be as light as possible. Weight governs the initial investment, the cost of shipping and site assembly, and the launch stresses. Weight limitation dictates the use of high-strength steel and designing

for high stress levels in different load and support conditions, which makes these machines potentially prone to instability.

Bridge erection machines are assembled and dismantled many times, in different conditions and by different crews. They are modified and adapted to new work conditions. Structural nodes and field splices are subjected to hundreds of load reversals. The nature of loading is often highly dynamic and the machines may be exposed to impacts and strong wind. Loads and support reactions are applied eccentrically, the support sections are often devoid of diaphragms, and most machines have flexible support systems. Indeed such design conditions are almost inconceivable in permanent structures subjected to such loads.

The level of sophistication of new-generation bridge erection machines requires adequate technical culture. Long subcontracting chains may lead to loss of communication, the problems not dealt with during planning and design must be solved on the site, the risks of wrong operations are not always evident in so complex machines, and human error is the prime cause of accidents.

Experimenting new solutions without the due preparation may lead to catastrophic results. Several bridge erection machines collapsed in the years, with fatalities and huge delays in the project schedule. A level of technical culture adequate to the complexity of mechanized bridge construction would save human lives and would facilitate the decision-making processes with more appropriate risk evaluations.

1. Introduction to Bridge Construction Methods

Every bridge construction method has its own advantages and weak points. In the absence of particular requirements that make one solution immediately preferable to the others, the evaluation of the possible alternatives is always a difficult task.

Comparisons based on the quantities of structural materials may mislead. The technological costs of processing of raw materials (labor, investments for special equipment, shipping and site assembly of equipment, energy) and the indirect costs related to project duration often govern in industrialized countries. Higher quantities of raw materials due to efficient and rapid construction processes rarely make a solution anti-economical.

Low technological costs are the reason for the success of the incremental launching method for PC bridges. Compared to the use of ground falsework, launching diminishes the cost of labor with similar investments. Compared to the use of an MSS, launching diminishes the investments with similar labor costs. In both cases launching diminishes the technological costs of construction and even if the launch stresses may increase the quantities of raw materials, the balance is positive and the solution is cost effective.

The construction method that comes closest to incremental launching is segmental precasting. The labor costs are similar but the investments are higher and the break-even point shifts to longer bridges. Spans of 30-50m are erected span-by-span with overhead or underslung launching gantries. Longer spans are erected as balanced cantilevers: self-

launching gantries reach 100-120m spans and lifting frames cover longer spans and curved bridges.

Heavy self-launching gantries are used for macro-segmental construction of 90-120m spans. Span-by-span erection of macro-segments requires props from foundations. Balanced cantilever erection involves casting long deck segments under the bridge for strand jacking into position. Both solutions require high investments.

On shorter bridges, prefabrication is limited to the girders and the deck slab is cast in-place. Precast beams are often erected with ground cranes. Sensitive environments, inaccessible sites, tall piers, steep slopes and inhabited areas often require assembly with beam launchers, and the technological costs increase.

LRT and HSR bridges with 30-40m spans may be erected by full-span precasting. The investment is so high that the break-even point is reached with hundreds of spans. The precasting plant delivers 2-4 spans per day for fast-track construction of large-scale projects. Optimized material and labor costs add to the high quality of factory production. Road carriers and ground cranes may erect four single-track U-girders (two LRT spans) every night. Heavy carriers with underbridge and gantries fed by SPMT's are the alternatives for ground delivery of HSR spans. Precast spans longer than 100m have been erected with floating cranes.

Medium-span PC bridges may also be cast in-place. For bridges with more than two or three spans it is convenient to advance in line by reusing the same formwork several times, and the deck is built span-by-span. Casting occurs in either fixed or movable formwork. The choice of equipment is governed by economic reasons as the labor cost associated with a fixed falsework and the investment requested for an MSS are both considerable.

Starting from the forties, the original wooden falsework has been replaced with modular steel framing systems. In spite of the refined support structures, labor may exceed 50% of the construction cost of the span. Casting on falsework is a viable solution only with inexpensive labor and small bridges. Obstruction of the area under the bridge is another limitation.

An MSS comprises a casting cell assembled onto a self-launching frame. MSS's are used for span-by-span casting of long bridges with 30-70m spans. If the piers are not tall and the area under the bridge is accessible, 90-120m spans can be cast with 45-60m MSS's supported onto a temporary pier in every span. Repetitive operations diminish the cost of labor, the quantities of raw materials are unaffected, and quality is higher than that achievable with a falsework.

Bridges crossing inaccessible sites with tall piers and spans up to 300m are cast in-place as balanced cantilevers. When the bridge is short or the spans exceed 100-120m the deck supports the form travelers. Overhead travelers are preferred in PC bridges while underslung machines are used in cable-stayed bridges and cable-supported arches. With long bridges and 90-120m spans, two longer casting cells may be suspended from a self-launching girder that also balances the cantilevers during construction.

2. Main Features of Bridge Erection Machines

The industry of bridge erection machines is a highly specialized niche. Every machine is initially conceived for a scope, every manufacturer has its own technological habits, and every contractor has preferences and reuse expectations. The country of fabrication also influences several aspects of design. Nevertheless, the conceptual schemes are not many.

Most beam launchers comprise two triangular trusses made of long welded modules. The diagonals may be bolted to the chords for easier shipping although site assembly is more expensive. Pins or longitudinal bolts are used for the field splices in the chords. New-generation single-girder machines allow robotized welding and have less support saddles and smaller winch-trolleys. 50m spans are rarely exceeded in precast beam bridges.

A launching gantry for span-by-span erection of precast segmental bridges also operates on 30-50m spans but the payload is much higher as the gantry supports the entire span during assembly. The payload of an MSS for in-place span-by-span casting is even higher as it also includes the casting cell, although the nature of loading is less dynamic.

Versatile twin-girder overhead machines comprise two trusses that suspend deck segments or the casting cell and carry runways for winch-trolleys or portal cranes. The field splices are designed for fast assembly and the modular nature of design permits alternative assembly configurations. These machines are easily reusable; however, their weight, labor demand and complexity of operations may suggest the use of more specialized machines on long bridges.

Lighter and more automated single-girder overhead machines are built around a central 3D truss or two braced I-girders. A light front extension controls overturning and a rear C-frame rolls along the completed bridge during launching. Single-girder overhead machines are compact and stable and require ground cranes only for site assembly. Telescopic configurations with a rear main girder and a front underbridge are also available for bridges with tight plan curves.

Underslung machines comprise two 3D trusses or pairs of braced I-girders supported onto pier brackets. Props from foundations may be used to increase the load capacity when the piers are short. A rear C-frame rolling over the completed bridge may be used to shorten the girders. Underslung machines offer a lower level of automation than the single-girder overhead machines and are affected by ground constraints and clearance requirements.

Span-by-span macro-segmental construction requires heavy twin-truss overhead gantries with a rear pendular leg that takes support onto the deck prior to segment lifting. Transverse joints at the span quarters and a longitudinal joint at bridge centerline divide 80-100m continuous spans into four segments. The segments are cast under the gantry with casting cells that roll along the completed bridge and are rotated and fed with the prefabricated cage at the abutment.

Overhead gantries for balanced cantilever erection of precast segments reach 100-120m spans. Compared to span-by-span erection, the payload is lower as no entire span is suspended from the gantry. The negative moment from the long front cantilever and the launch stresses on so long spans govern design. Varying-depth trusses are structurally more efficient while constant-depth trusses are easier to reuse on different span lengths. Stay cables are rarely used in new-generation machines.

Overhead MSS's for balanced cantilever bridges operate in a similar way. Two long casting cells suspended from a self-launching girder shift symmetrically from the pier toward midspan to cast the two cantilevers. After midspan closure and launching to the next pier, the casting cells are set close to each other to cast the new double pier-head segment. These machines can be easily modified for strand-jacking of macro-segments cast on the ground.

The bridge itself can support lifting frames for balanced cantilever erection of precast segments or form travelers for in-place casting. These light machines are used in short or curved bridges, PC spans up to 300m, and cable-stayed bridges. Lifting frames and form travelers permit erection of several hammers at once and different erection sequences than from abutment to abutment, but they require more prestressing and increase the demand for labor and ground cranes.

Carriers with underbridge and heavy gantries fed by SPMT's are used to erect precast spans. Spans are rarely longer than 40m in LRT and HSR bridges and 50m in highway bridges due to the prohibitive load on the carriers and the bridge. Longer spans have been handled with floating cranes when the bridge length permitted amortization of such investments.

3. Beam Launchers

The most common method for erecting precast beams is with ground cranes. Cranes usually give the simplest and most rapid erection procedures with the minimum of investment, and the deck may be built in several places at once. Good access is necessary along the entire length of the bridge to position the cranes and deliver the girders. Tall piers or steep slopes make crane erection expensive or prevent it at all.

The use of a beam launcher solves any difficulty. A beam launcher is a light self-launching machine comprising two triangular trusses. The truss length is about 2.3 times the typical span but this is rarely a problem as the gantry operates above the deck (Figure 1). Beam launchers easily cope with variations in span length and deck geometry, plan curvatures and ground constraints. Crossbeams support the gantry at the piers and allow transverse shifting to erect the edge beams and to traverse the gantry for launching along curves.

Two winch-trolleys span between the top chords of the trusses and lodge two winches each. The main winch suspends the beam and a translation winch acting on a capstan moves the trolley along the gantry. A third trolley carries an electric generator that feeds gantry operations. When the beams are delivered at the abutment and the vertical

movements are therefore small, the main winches may be replaced with less expensive long-stroke hydraulic cylinders.



Figure 1. 102m, 90ton launcher for 45m, 120ton beams (Comtec)

A beam launcher operates in one of two ways depending on how the beams are delivered. If the beams are delivered on the ground, the launcher lifts them up to the deck level and places them onto the bearings. If the beams are delivered at the abutment, the launcher is moved back to the abutment and the winch-trolleys are moved to the rear end of the gantry. The front trolley picks up the front end of the beam and moves it forward with the rear end suspended from a straddle carrier. When the rear end of the beam reaches the rear winch-trolley, the trolley picks it up to release the carrier.

The longitudinal movement of the gantry is a two-step process. Automatic clamps block the trusses to the crossbeams and the winch-trolleys move the beam one span ahead; then the winch-trolleys are anchored to the crossbeams, the blocks are released and the translation winches push the trusses to the next span. Redundancy of anchorages is necessary in both phases for safe launching along inclined planes. The sequence can be repeated many times so when the beams are delivered at the abutment, the gantry can place them several spans ahead. When the bridge is long, moving the gantry over many

spans slows the erection down and may be faster to cast the deck slab as soon as the beams are placed and to deliver the next beams along the completed bridge.

Truss deflections at landing at the piers are recovered with alignment wedges. The alignment force is small but the support saddles must be anchored to avoid displacements or overturning. Realignment may also be achieved with long-stroke cylinders that rotate arms pinned to the tip of the truss. Similar devices are also applied to the rear end of the gantry to release the support reaction when launching forward and to recover the deflection when launching backward.

New-generation single-girder launchers are based on two braced I-girders. The main girder is less expensive than two triangular trusses due to robotized welding, the winch-trolleys are smaller, the number of support saddles halves, and the crossbeams are shorter. Lightened launching noses may be attained with laser-cut windows in the webs to avoid hand welding. A C-frame supports the rear end of the gantry and allows the beams to pass through when delivered along the completed bridge. The C-frame is not necessary when the beams are delivered on the ground as the launcher lifts and shifts them into position within the same span (Figure 2).



Figure 2. 74m, 98ton single-girder shifter for 28m, 60ton beams (Deal)

Crossbeams anchored to the pier caps carry rails for lateral shifting of the gantry. The crossbeams have lateral overhangs for placement of the edge girders and to traverse the gantry for launching along curves. Adjustable support legs located so as not to interfere with the precast beams are used to set the crossbeams horizontal. Some launchers have

light service cranes at the ends of the trusses to reposition the crossbeams without any need for ground cranes.

The support saddles comprise bottom rollers that shift laterally along the crossbeam and top rollers that support the truss. Equalizer beams allow the top rollers to cope with the flexural rotations in the truss and the gradient of the launch plane. A vertical pivot connects the two roll assemblies to allow rotations in the horizontal plane. Lateral shifting along the crossbeams is achieved with capstans or light long-stroke cylinders.

Automatic clamps block the trusses to the crossbeams during winch-trolley operations. Launching occurs along inclined planes and breaking of any component of the tow system would leave the gantry unrestrained on low-friction supports. Redundancy of tow systems involves oversizing and slow operations.

-
-
-

TO ACCESS ALL THE **60 PAGES** OF THIS CHAPTER,
Visit: <http://www.eolss.net/Eolss-sampleAllChapter.aspx>

Bibliography

AASHTO (2003). *Guide Specifications for Design and Construction of Segmental Concrete Bridges*. American Association of State Highway and Transportation Officials (AASHTO). [This standard provides guidance on design and construction of segmental PC bridges in the U.S. It includes loads and load combinations for analysis of staged construction].

AASHTO (2008). *Construction Handbook for Bridge Temporary Works*. American Association of State Highway and Transportation Officials (AASHTO). [This manual provides general information for falsework construction in the U.S.].

AASHTO (2008). *Guide Design Specifications for Bridge Temporary Works*. American Association of State Highway and Transportation Officials (AASHTO). [This manual provides design guidance for ground falsework and other temporary works for bridge construction in the U.S.].

AASHTO (2010). *LRFD Bridge Design Specifications*. American Association of State Highway and Transportation Officials (AASHTO). [This standard rules bridge design practice in the U.S. It includes some guidance on bridge erection equipment].

AASHTO (2010). *LRFD Bridge Construction Specifications*. American Association of State Highway and Transportation Officials (AASHTO). [This standard rules bridge construction in the U.S. It includes some guidance on bridge erection equipment].

ACI (2004). *Guide to Formwork for Concrete*. American Concrete Institute (ACI). [This manual provides general information and design guidance for formwork].

ASBI (2008). *Construction Practices Handbook for Concrete Segmental and Cable-Supported Bridges*. American Segmental Bridge Institute (ASBI). [This handbook is an international reference for construction of segmental PC bridges. It provides broad information on the technical and technological aspects of most erection methods for PC bridges].

AISC (2006). *Base Plate and Anchor Rod Design*. American Institute of Steel Construction (AISC). [This booklet provides guidance for design of base plates and anchor rods].

Boggs, D.; Peterka, J. (1992). *Wind Speeds for Design of Temporary Structures*. Proceedings of the 10th ASCE Structures Congress, San Antonio, USA. American Society of Civil Engineers (ASCE). [This paper defines wind load to be used in the design of falsework and other types of temporary structures].

BSI (1982). *Code of Practice for Falsework*. British Standards Institute (BSI). [This booklet provides general design and technical guidance for falsework in the U.K.].

BSI (2002). *Eurocode 0. Basis of Structural Design*. British Standards Institute (BSI). [EC:0 provides general guidance for design of pedestrian, highway and HSR bridges. EC:0 has been updated with Amendment 1 in 2005. The EC countries integrate the Eurocodes with National Annexes, available in different languages].

BSI (2004). *Eurocode 1. Actions on Structures*. British Standards Institute (BSI). [EC:1 provides state-of-the-art guidance on the actions to be considered for the design of bridges, cranes, machinery, silos and tanks: general actions on structures (EC:1.1-1), actions on structures exposed to fire (EC:1.1-2), snow loads (EC:1.1-3), wind actions (EC:1.1-4), thermal actions (EC:1.1-5), general actions during construction (EC:1.1-6), accidental actions (EC:1.1-7), traffic load on bridges (EC:1.2), actions induced by cranes and machinery (EC:1.3), and actions on silos and tanks (EC:1.4). The EC countries integrate the Eurocodes with National Annexes, available in different languages].

BSI (2005). *Eurocode 2. Design of Concrete Structures*. British Standards Institute. [EC:2 provides state-of-the-art guidance for the design of concrete and PC structures: general rules and rules for buildings (EC:2.1-1), general rules for structural fire design (EC:2.1-2), design and detailing rules for concrete bridges (EC:2.2), and design rules for liquid retaining and containment structures (EC:2.3). The EC countries integrate the Eurocodes with National Annexes, available in different languages].

BSI (2005). *Eurocode 3. Design of Steel Structures*. British Standards Institute (BSI). [EC:3 provides state-of-the-art guidance for the design of steel structures: general rules (EC:3.1-1), general rules for structural fire design (EC:3.1-2), supplementary rules for cold-formed members and sheeting (EC:3.1-3), supplementary rules for stainless steels (EC:3.1-4), design rules for plated structural elements (EC:3.1-5), supplementary rules for shell structures (EC:3.1-6), supplementary rules for planar plated structural elements under out-of-plane loading (EC:3.1-7), design of joints (EC:3.1-8), design for fatigue (EC:3.1-9), material toughness and through-thickness properties (EC:3.1-10), structures with tension components (EC:3.1-11), steel bridges (EC:3.2), towers and masts (EC:3.3-1), chimneys (EC:3.3-2), silos (EC:3.4-1), tanks (EC:3.4-2), pipelines (EC:3.4-3), piling (EC:3.5) and crane supporting structures (EC:3.6). The EC countries integrate the Eurocodes with National Annexes, available in different languages].

BSI (2005). *Eurocode 8. Design of Structures for Earthquake Resistance. Bridges*. British Standards Institute (BSI). [EC:8 includes probabilistic equations for evaluation of the reduced seismic demand during construction based on shorter return periods related to construction duration. The EC countries integrate the Eurocodes with National Annexes, available in different languages].

BSI (2008). *Code of Practice for Temporary Works Procedures and the Permissible Stress Design of Falsework*. British Standards Institute (BSI). [This booklet provides general information and design guidance for falsework in the UK].

BSI (2009). *Execution of Concrete Structures*. British Standards Institute (BSI). [This booklet contains guidance on construction of concrete and PC structures].

CEN (2008) *Falsework. Performance Requirements and General Design*. European Committee for Standardization (CEN). [This booklet provides general design guidance and performance requirements for falsework].

CEN (2009). *Design of Fastenings for Use in Concrete*. European Committee for Standardization (CEN). [This booklet provides guidance on the design of concrete fasteners].

CSA (1975). *Falsework for Construction Purposes. Design*. Canadian Standards Association (CSA). [This booklet provides general design guidance for design of falsework in Canada].

CSA-S6-00 (2000). *Canadian Highway Bridge Design Code*. Canadian Standards Association (CSA). [This standard provides comprehensive guidance for the design of bridges in Canada].

CIRIA (1977). *Rationalization of Safety and Serviceability Factors in Structural Codes*. Construction Industry Research and Information Association (CIRIA). [This booklet is not directly related to bridge erection equipment, but calibration of load and resistance factors is a major issue in defining future international design standards for bridge erection equipment].

Ellingwood, B. (2008). *Reliability Based Codes in the United States. Challenges to Professional Engineering Practice*. Proceedings of the 4th International ASRANet Colloquium on Integrating for Structural Analysis, Risk & Reliability, Athens, Greece, 2008. [This publication identifies the main challenges of US standards based on reliability].

FEM 1.001 (1987) *Règles pour le calcul des appareils de levage*. Federation Europeenne de la Manutention (FEM). [This standard is an international reference for the design of launching gantries, lifting frames, span carriers, beam launchers, winch-trolleys, portal cranes, strand-jacking platforms and other types of heavy lifters. Classification of structural and mechanical components is compatible with design of bridge erection machines per local standards. Available in three languages].

FIB (2009) *Formwork and Falsework for Heavy Construction. Guide to Good Practice*. International Federation for Structural Concrete (FIB). [This manual mainly addresses form design and ground falsework].

Hewson, N.R. (2003) *Prestressed Concrete Bridges: Design and Construction*. Thomas Telford. [This book contains detailed information on the technological aspects of several bridge erection methods].

Hill, H. (2004). *Rational and Irrational Design Loads for “Temporary” Structures*. Practice Periodical on Structural Design and Construction, 9, 125-129. [This paper critically reviews the reliability of the design loads used for temporary constructions].

HSE (2001). *Reducing Risks, Protecting People. HSE’s Decision-Making Process*. Health and Safety Executive (HSE). [This booklet provides general information on risk analysis in the decision-making process].

HSE (2011). *Preventing Catastrophic Events in Construction*. Health and Safety Executive (HSE). [This manual provides HSE guidance of accident prevention in construction].

ISO (2009). *Risk Management - Principles and Guidelines*. International Organization for Standardization (ISO). [This manual identifies general principles and guidelines of risk management].

ISO (2009). *Risk Management - Risk Assessment Techniques*. International Organization for Standardization (ISO). [This manual identifies general risk assessment techniques and their effectiveness in risk mitigation].

Ratay, R. (2009). *Forensic Structural Engineering Handbook*. McGraw Hill Professional. [This book presents an in-depth coverage of forensic engineering].

Reason, J. (1990). *Human Error*. Cambridge University Press. [This book investigates the most common causes of human error].

Rosignoli, M. (1997). *Incremental Bridge Launching*. Concrete International, 19-2, 36-40. American Concrete Institute (ACI). [This paper compares alternative construction methods for PC bridges in relation to the components of bridge construction cost].

Rosignoli, M. (1997). *Influences of the Incremental Launching Construction Method on the Sizing of Prestressed Concrete Bridge Decks*. Proceedings of the Institution of Civil Engineers, Structures and Buildings. The Institution of Civil Engineers (ICE). [This paper discusses the impacts of incremental launching construction on the dimensions and quantities of structural materials of PC bridges].

Rosignoli, M. (1997). *Solution of the Continuous Beam in Launched Bridges*. Proceedings of the Institution of Civil Engineers, Structures and Buildings, 122, 390-398. The Institution of Civil Engineers (ICE). [This paper describes the Reduced Transfer Matrix method for analysis of temporary erection stresses in bridges built by incremental launching. The RTM method can analyze the hyperstatic launch stresses in every type of self-launching machine].

Rosignoli, M. (1998). *Nose-Deck Interaction in Launched Prestressed Concrete Bridges*. ASCE Journal of Bridge Engineering, 3-1, 21-27. American Society of Civil Engineering (ASCE). [This paper provides closed-form equations for analysis of the interaction between the PC bridge and the hydraulic launching nose and describes optimization techniques for nose-deck interaction].

Rosignoli, M. (1998). *Serio River Bridge, Creep and Incremental Launch*. Proceedings of the Institution of Civil Engineers, Structures and Buildings, 128, 1-11. The Institution of Civil Engineers (ICE). [This paper describes the effects of creep of concrete on the temporary launch stresses and the modifications of launch equipment to overcome creep deflections due to work stoppage].

Rosignoli, M. (1998). *Site Restrictions Challenge Bridge Design*. Concrete International, 20-8, 40-43. American Concrete Institute (ACI). [This paper describes the erection equipment for two road bridges and a cable-stayed LRT bridge built by incremental launching over six railroads with the help of cable-stayed temporary piers].

Rosignoli, M. (1998). *Misplacement of Launching Bearings in P.C. Launched Bridges*. ASCE Journal of Bridge Engineering, 3-4, 170-176. American Society of Civil Engineering (ASCE). [This paper provides closed-form equations for analysis of the temporary stresses generated by misplacement of the launching bearings during incremental launching construction of PC box girders].

Rosignoli, M. (1999). *Prestressing Schemes for Incrementally Launched Bridges*. ASCE Journal of Bridge Engineering, 4-2, 107-115. American Society of Civil Engineering (ASCE). [This paper illustrates the prestressing schemes used to overcome the temporary launch stresses in PC bridges built by incremental launching].

Rosignoli, M. (1999). *Reduced Transfer Matrix Method for Analysis of Launched Bridges*. ACI Structural Journal, 96-4, 603-608. American Concrete Institute (ACI). [This paper deepens the discussion of the RTM method for the analysis of temporary launch stresses in PC bridges].

Rosignoli, M. (1999). *Presizing of Prestressed Concrete Launched Bridges*. ACI Structural Journal, 96-5, 705-710. American Concrete Institute (ACI). [This paper discusses the impacts of incremental launching construction on the dimensions and quantities of structural materials in PC bridges in relation to the main features of launch equipment].

Rosignoli, M. (1999). *Nose Optimization in Launched Bridges*. Proceedings of the Institution of Civil Engineers, Structures and Buildings, 134, 373-375. The Institution of Civil Engineers (ICE). [This paper summarizes the criteria for optimal design of the steel noses for PC bridges built by incremental launching].

Rosignoli, M. (2000). *Thrust and Guide Devices for Launched Bridges*. ASCE Journal of Bridge Engineering, 5-1, 75-83. American Society of Civil Engineering (ASCE). [This paper illustrates strand jacking systems and friction launchers used for the incremental launching of PC bridges. It also describes launch bearings and lateral guides and provides guidance for the most appropriate choice and design of launch equipment].

Rosignoli, M. (2001). *Deck Segmentation and Yard Organization for Launched Bridges*. ACI Structural Journal, 23-2, 2-11. American Concrete Institute (ACI). [This paper compares alternative segmentations of PC bridges built by incremental launching and their impacts on yard organization and the investments for erection equipment].

Rosignoli, M. (2002). *Bridge Launching*. Thomas Telford. [This 340-page book is devoted to the incremental launching of bridges and related erection equipment. It covers design and construction of PC, steel, composite, and prestressed composite box girders with corrugated plate webs and concrete slabs].

Rosignoli, M. (2007). *Monolithic Launch of the Reggiolo Overpass*. ACI Structural Journal, 2, 61-65. American Concrete Institute (ACI). [This paper describes design of bridge and erection equipment for a multi-cellular trapezoidal span launched over an electrified railroad with the help of a temporary pier].

Rosignoli, M.; Rosignoli, C. (2007). *Launch and Shift of the Tiziano Bridge*. ACI Structural Journal, 29-10, 44-49. American Concrete Institute (ACI). [This paper describes design of bridge and erection equipment for a 200m twin-box-girder bridge built by launching a first box girder, shifting the girder laterally, launching a second box girder, and connecting the two girders with a central concrete stitch].

Rosignoli, M. (2007). *Robustness and Stability of Launching Gantries and Movable Shuttering Systems – Lessons Learned*. Structural Engineering International, 17, 133-140. [This paper deals with stability and robustness of self-launching gantries and MSS's. It compares the time-integration techniques for dynamic analysis of out-of-plane buckling and provides additional information on the analysis of progressive collapse].

Rosignoli, M. (2010). *Self-Launching Erection Machines for Precast Concrete Bridges*. PCI Journal. Precast/Prestressed Concrete Institute (PCI). Winter 2010, 36-57. [This long paper presents state-of-the-art information on beam launchers, self-launching gantries and span carriers for precast bridges].

Rosignoli, M. (2010). *Chair's introduction*. 1st IABSE International Seminar “*State-of-the-art Bridge Deck Erection: Safe and Efficient Use of Special Equipment*” Singapore, November 2010. International Association for Bridge and Structural Engineering (IABSE). [Chair's introduction focused on the absence of international standards for design and operations of bridge erection equipment and the impacts on safety of workers and quality of bridges].

Rosignoli, M. (2011). *Industrialized Construction of Large Scale HSR Projects: the Modena Bridges in Italy*. Structural Engineering International, 21-4. [This paper deals with the project organization for full-span precasting of 755 spans of HSR bridges in 30 months under global warranty (time, cost and quality) and the criteria used for the independent design checking of equipment and the QA/QC qualification of casting and erection processes].

Rosowsky, D. (1995). *Estimation of Design Loads for Reduced Reference Periods*. Structural Safety, 17, 17-32. [This paper provides guidance on the analysis of meteorological loads during erection].

SAA (1995). *Formwork for Concrete*. Standards Association of Australia (SAA). [This manual provides general guidance and design instructions for falsework].

SAA (2007). *Bridge Design*. Standards Association of Australia. [This standard provides guidance for the design of bridges in Australia].

Scheer, J. (2010). *Failed Bridges: Case Studies, Causes and Consequences*. Wiley VCH. [This book contains updated information on bridge failures].

Sexsmith, R. (1988). *Reliability During Temporary Erection Phases*. Engineering Structures, 20, 999-1003. [This paper deals with structural safety and other reliability aspects of staged construction].

Sexsmith, R.; Reid, S. (2003). *Safety Factors for Bridge Falsework by Risk Management*, Structural Safety, 25, 227-243. [This paper describes a risk-management-driven approach to the load and resistance factors for the design of temporary structures].

Starossek, U.; Wolff, M. (2005). *Progressive Collapse: Design Strategies*. Proceedings of IABSE Symposium, Structures and Extreme Events, Lisbon, Portugal. International Association for Bridge and Structural Engineering (IABSE). [This paper illustrates design strategies to mitigate the risk of progressive collapse and to provide adequate robustness of structures].

Starossek, U. (2006). *Progressive Collapse of Structures: Nomenclature and Procedures*. Structural Engineering International, 16, 113-117. [This paper defines nomenclature and procedures related to progressive collapse].

Starossek, U. (2009). *Progressive Collapse of Structures*. Thomas Telford. [This book examines causes, analysis methods and design approaches for prevention of progressive collapse of structures].

Biographical Sketch

Marco Rosignoli received his Doctorate in Civil Engineering *cum laude* at the University of Ancona (Italy) in 1981. From 1982 to 1997 he served as construction manager, project manager, bridge department lead and technical director with prime European bridge contractors. From 1997 to 2006 he worked as an international free-lance consultant for the design and independent design checking of major bridges and bridge erection machines. He is serving as principal bridge engineer at HNTB Corp. since 2006. Assistant to bridge designers, contractors and owners in 21 countries and 4 continents, expert in bridge design and construction technologies, and international authority on the incremental launching of

bridges, Dr. Rosignoli is author of 2 books and 80+ publications on mechanized bridge construction. Author of Chapter 6 of ASBI *Construction Practices Handbook* and member of ASBI Technical Advisory Committee, he has set up and is chairing IABSE working group WG-6 *Bridge Construction Equipment* for the 2009-2013 period.

UNESCO – EOLSS
SAMPLE CHAPTERS